

NPS microgrid hybrid inverter



KEY

- Internal integration PV interfaces, battery interfaces, load interfaces and grid interfaces
- Easy expansion, support PV flexible configuration.
- DC-coupled solution with 2% higher system efficiency.
- Support single-phase and three-phase load power supply at the same time.
- Control power AC and DC redundant power supply, the system is more secure and reliable.

APPLICATIONS

- » » Off-grid mine
- » » Off-grid island
- » » Nomadic farm
- » » Villages without electricity



NPS microgrid series



AC(on-grid)						
Model	NPS0030	NMPS005	NPS0100	NPS0150	NPS0250	NPS0500
Max output power (kVA)	33	55	110	165	275	550
Rate output power (kW)	30	50	100	150	250	500
Rated voltage(V)	400					
Voltage range (V)	320~460					
Rated current (A)	43	72	144	216	361	722
Rated frequency (Hz)	50/60					
Frequency range (Hz)	45~55/55~65					
THDi	<3%					
Power factor	1lagging-1leading (Settable)					
AC connection	3W+N+PE					
Transformer ratio	100/400	200/400	270/400	270/400	270/400	315/400

AC(off-grid)						
Max output power (kVA)	33	55	110	165	275	550
Rated power (kW)	30	50	100	150	250	500
Rated voltage (V)	400					
Rated current (A)	43	72	144	216	361	722
THDu	≤1% linear; or≤5% nonlinear					
Rated frequency (Hz)	50/60					
Overload capacity	110% long-term, 120% 1min					

PV input						
Max.PV input voltage (V)	1,000					
Max.PV power (kW)	36/72	60/120	120/180/240	120/180/240	300/360	600/660/720
MPPT module quantity	1/2	1/2	2/3/4	2/3/4	5/6	10/11/12
MPPT voltage range (V)	250-850					
MPPT voltage range@full load (V)	450-850					

Battery						
Battery voltage range (V)	250~850	320~850	420~850	420~850	420~850	500~850
Max. charging power (kW)	36/72	60/120	120/180/240	120/180/240	300/360	600/660/720

General data						
Dimension W*D*H (mm)	800*800*1,900	800*800*1,900	1,200*800*2,050	1,200*800*2,050	(600*720*2,050)*1+ 1,200*800*2,050	(600*720*2,050)*2+ 1,600*1050*2,050
Net weight (kg)	576/607	720/750	1,120/1,150/1,180	1,250/1,280/1,310	1,980/2,010	3,265/3,295/3,325
Operation temperature (°C)	-30 ~ 55					
Relative humidity	0 ~95% non-condensing					
Ingress protection	IP20					
Noise emission (dB)	<70					
Operating altitude	<5000m(>3,000 Derating)					
Cooling	Air Cooling					

Display and communication	
Display	LCD touch-screen
BMS communication	RS485, CAN
EMS communication	RS485, TCP/IP
Certificates	EN62109-1/-2, EN62477-1, EN61000-6-2, EN61000-6-4, South Africa NRS097-2-1:2017, Pakistan & India IEC61727, IEC62116, IEC 61683

NPS PV and battery configuration principles:

- > Boost mode configuration principle - open voltage at low temperature at the limit of PV installation * number of PV panels in series ≤ the lowest voltage of the battery;
- > Buck mode configuration principle - the maximum power operating voltage at the extreme high temperature of PV installation≥ the highest voltage of the battery;
- > The PV and battery configurations of MPS must comply with the above configuration principles.